

multi pro

Exhaust duct cleaning system

Advanced pneumatic rotary brush unit, with **integrated active foam generator**, for the cleaning of kitchen exhaust ducts and industrial facilities.

Integrated foaming system

Generates the active foam that adheres to the entire duct surface. There is no need for additional equipment.

Comegras storage

Place the degreaser container that generates the active foam.



Brushes

Different materials and sizes for all types of ductwork. **DUO Square system** for effective cleaning in square ducts.



LED indicator

Shows the status of the machine.

HMI screen

Control all equipment functions

Shaft guard

Facilitates its take-up and protects it when you are on the move.

PNEUMATIC

For ducts up to

1000 mm

Hose length

30 meters

Self-leveling camera

Provide upright images at all times even when the camera is tilted. Visualizes and cleans **at the same time**. [Optional]





AIR COMPRESSOR AR20
Paddle system. [Not included]

OPTIONALES ACCESORIES ▼



WRIST REMOTE CONTROL
Operate by one person
AC3303604




BRUSH CENTERING DEVICE.
For ducts from 500 mm |
19.7 inch to 1000 mm |
39.3 inch. AC33031030



VISUALIZATION PACK. Visualization system, camera harness, camera and carrying case.
AC33031031

CONSUMABLES ▼



PACK 5 MIXED BRUSHES. Steel + nylon. For carbonized grease.
Ø200 | 300 | 400 | 500 | 600 mm
Ø7.8 | 11.8 | 15.7 | 19.7 | 23.6 inch
CP1302828



PACK 4 BRUSHES EXTREME.
Brushes for extreme cleaning.
Includes case.
Ø300 | 400 | 500 | 600 mm
Ø11.8 | 15.7 | 19.7 | 23.6 inch
CP2300515

PACK 5 BRUSHES PBT. Indicated for fatty residue of medium-high hardness. High abrasion power.
Ø200 | 300 | 400 | 500 | 600 mm
Ø7.8 | 11.8 | 15.7 | 19.7 | 23.6 inch
CP1203030



PACK 5 NYLON BRUSHES
Indicated for the removal of medium-hard grease.
Ø300 | 400 | 600 | 700 | 800 mm
Ø11.8 | 15.7 | 23.6 | 27.5 | 31.5 inch
Cp1101520

COMEGRAS
Ultraconcentrated degreaser.
10 kg | 22 lb Jerrycan. PQ8100122

TECHNICAL FEATURES **multipro**

Motor supply [Maximum power]	Compressed air 300 l/min 8 bar 10,6 cfm – 8 bar
Rotation speed when empty	500 r.p.m.
Maximum torque	11,6 Nm 102,7 ibf-in
Noise level	< 70 dB
Direction of rotation	Right Left
Control system	Electropneumatic
Control panel	HMI screen
Hose length	30 m 98,43 ft
Structure material	Stainless steel
Dimensions [L x H x W]	1162 x 1244 x 430 mm 46 x 49 x 17 inch
Weight	73 kg 161 lb