

multi^{pro}

Exhaust duct cleaning system

Advanced pneumatic rotary brush unit for the cleaning of kitchen exhaust ducts and industrial facilities.

Brushes

Different materials and sizes for all types of ductwork.
DUO Square system for effective cleaning in square ducts.



PNEUMATIC

For ducts up to

1000 mm

Hose length

30 m

Self-leveling camera

Provide upright images at all times even when the camera is tilted. Visualizes and cleans at the same time. (Optional)





WRIST REMOTE CONTROL

Included accessory that allows the equipment to be controlled by a single operator.

OPTIONALES ACCESORIES ▼



WRIST REMOTE CONTROL

Operate by one person

AC3303616



BRUSH CENTERING DEVICE.

For ducts from 500 mm | 19.7 inch to 1000 mm | 39.3 inch


AC3303130



VISIOPRO. Visualization system, camera harness, camera and carrying case.

SV3331035 SV-MUL

CONSUMABLES ▼



PACK 5 MIXED BRUSHES.

Steel +nylon. For carbonized grease. Ø200 | 300 | 400 | 500 | 600 mm. Ø7.8 | 11.8 | 15.7 | 19.7 | 23.6 inch
CP1302828



PACK 5 BRUSHES EXTREME.

Brushes for extreme cleaning. Ø300 | 400 | 500 | 600 /700 mm Ø11.8 | 15.7 | 19.7 | 23.6 | 27.5 inch
CP2300515

PACK 5 BRUSHES PBT.

Indicated for fatty residue of medium-high hardness. High abrasion power. Ø200 | 300 | 400 | 500 | 600 mm Ø7.8 | 11.8 | 15.7 | 19.7 | 23.6 inch
CP1101520

PACK 5 NYLON BRUSHES

Indicated for the removal of medium-hard grease. Ø300 | 400 | 600 | 700 | 800 mm Ø11.8 | 15.7 | 23.6 | 27.5 | 31.5 inch
CP1203030

TECHNICAL FEATURES

Motor supply [Maximum power]	Compressed air 300 l/min 8 bar 10,6 cfm – 8 bar
Rotation speed when empty	500 r.p.m.
Maximum torque	11,6 Nm 102,7 lbf.in
Noise level	< 70 dB
Direction of rotation	Right Left
Control panel	HMI screen
Control system	Electropneumatic
Hose length	30 m 98 ft
Structure material	Stainless steel
Dimensions [L x H x W]	1118 x 440 x 1172 mm 44 x 17 x 46 inch
Weight	73 kg 161 lb