




ACCESS DOORS AND DUCT DRAINS

EN

TEINNOVA
passion for innovation®



contents



01

ACCESS DOORS FOR INSPECTION
AND CLEANING FOR AIR DUCTS



02

ACCESS DOORS FOR INSPECTION
AND CLEANING OF EXTRACTION SYSTEMS





Description

Access doors for the inspection and cleaning of the interior of air conditioning and ventilation ducts, easily and quickly operated without the need for any tools, they achieve a perfect seal thanks to their double body and airtight gasket, they allow you to comply with current standards.


Regulations

1. Duct networks must be equipped with access doors in accordance with standard UNE-ENV 12097 to allow for cleaning and disinfection.
2. Elements installed in a duct network must be removable and have an access door or a removable conduit section to allow for maintenance operations. They must be placed at least every 10 m.
3. False ceilings must have inspection hatches that match the position of the doors in the ducts and the devices located in them.

Technical info



- Structure material:** Galvanized sheet metal.
- Knob material:** Polyamide plastic.
- Seal material:** Polyethylene.
- Available sizes:** 150x250; 300x200; 400x300.
- Range of curvatures:** From 100 to 800 mm in diameter.



01

ACCESS DOORS FOR INSPECTION AND CLEANING FOR AIR DUCTS

AIR DUCTS



01

Access doors for ducts




TYPE OF DUCT	Size A x B mm and weight	Diameter Ød in mm	Product code
DOORS FOR FLAT DUCTS 	200 x 100 mm / 0,5 kg	---	AC6102010
	250 x 150 mm / 0,5 kg	---	AC6102515
	300 x 200 mm / 0,5 kg	---	AC6103020
	400 x 300 mm / 1 kg	---	AC6104030


DESCRIPTION

Access doors for the inspection and cleaning of the interior of air conditioning and ventilation ducts, easily and quickly operated without the need for any tools, they achieve a perfect seal thanks to their double body and airtight gasket, they allow you to comply with current standards.

TYPE OF DUCT	Size A x B mm and weight	Diameter Ød in mm	Product code
DOORS FOR CURVED DUCTS 	250 x 150 mm / 1 kg	Ø200 - Ø250	AC6112525
	300 x 200 mm / 1,3 kg	Ø315 - Ø355	AC6113035
	300 x 200 mm / 1,3 kg	Ø400 - Ø450	AC6113045
	400 x 300 mm / 1,8 kg	Ø500 - Ø560	AC6114056
	400 x 300 mm / 1,8 kg	Ø630	AC6114063




1. Apply the self-adhesive template to the duct wall [included with the product]. The prices shown do not include VAT or transport



2. Cut around the edge of the template to create the opening [see cutting tool on page 6]



3. Unscrew the knobs to their limit, insert the door slightly angled and tighten the knobs to their limit.





12 ACCESS DOORS FOR INSPECTION AND CLEANING

OF EXTRACTION SYSTEMS



02

Access doors for ducts




DESCRIPTION


Access doors for the inspection and cleaning of the interior of fume extraction ducts, can be used simply and quickly, with no tools, they provide a perfect seal thanks to their double body and their fire resistant ceramic fibre seal, with metallic knobs they can comply with current regulations.

TYPE OF DUCT	Size A x B mm and weight	Diameter Ød in mm	Product code
DOORS FOR FLAT DUCTS 	250 x 150 mm / 0,5 kg	---	AC6122515
	300 x 200 mm / 0,5 kg	---	AC6123020
	400 x 300 mm / 2,2 kg	---	AC6124030

TYPE OF DUCT	Size A x B mm and weight	Diameter Ød in mm	Product code
DOORS FOR CURVED DUCTS 	250 x 150 mm / 1 kg	Ø200 - Ø250	AC6132525
	300 x 200 mm / 1 kg	Ø400 - Ø450	AC6133045
	300 x 200 mm / 1,3 kg	Ø500	AC6133050



1. Apply the self-adhesive template to the duct wall [included with the product]. The prices shown do not include VAT or transport



2. Cut around the edge of the template to create the opening [see cutting tool on next page]



3. Unscrew the knobs to their limit, insert the door slightly angled and tighten the knobs to their limit.

TEiNOVA
passion for innovation®

