COIL FEEDING SYSTEMS

SACFORM

AGMline



MECHANICAL DECOILERS

Mechanical decoiler group has screw shaft clamping and expansion system from center. Working capacity range is between 750 kg to 4.000 kg. Motorized, pneumatic snubber arm and brake models are available. Mechanical decoilers take up less space and have minimum operating cost for companies

- Manual Mechanical Mandrel Expansion Speed Control System
- Brake System Adjustable Coil Width
- Loading Capacity Between 750 kg to 4.000 kg (Optional Feature)
- Pneumatic Coil Hold-Down

Model	Max. Material Width (mm)	Coil Inside Diameter (mm)		Max. Coil Outside Diameter (mm)	Coil Weight(kg)	Motor	Snubber Arm
		Min	Max				
RM750M	20-300	300	550	1400	750	v	Optional
RM1500M	20-400	350	550	1400	1500	v	Optional
RM2500M	30-500	400	550	1400	2500	v	Optional
RM3000M	30-600	450	550	1400	3000	v	Optional
RM4000KM-PUB	70-600	470	530	1500	4000	v	Optional
RM4000KM-PUB	70-800	470	530	1500	4000	v	Optional
RM4000KM-PUB	100-1000	470	530	1500	4000	v	Optional