

HYDRAULIC DECOILERS & LOADING CAR

Hydraulic Decoilers with loading cars have a working capacity of 6.000 kg to 25.000 kg. Their expansion system is hydraulic and working systems are controlled by a joystick arm. Loading cars work with a motorized system and the speed control unit comes as a standard optional feature.

- Loading Capacity of 6.000 kg to 25.000 kg with Hydraulic Mandrel Expansion
- Joystick Control System
- Coil Snubber Arm (Coil Support Arm Speed Control Unit)
- Photoelectric Sensor (Adjustable)

Model	Max. Material Width (mm)	Coil Inside Diameter (mm)		Max. Coil Outside Diameter (mm)	Coil Weight (kg)	Mandrel Expansion	Motor	Snubber Arm
		Min	Max					
RMH6000HM-PUB	75-600	490	550	1300	6000	Hydraulic	✓	✓
RMH6000HM-PUB	100-800	490	550	1300	6000	Hydraulic	✓	✓
RMH6000HM-PUB	100-1000	490	550	1300	6000	Hydraulic	✓	✓
RMH10000HM-PUB	100-1000	490	550	1300	10000	Hydraulic	✓	✓
RMH10000HM-PUB	100-1300	490	550	1300	10000	Hydraulic	✓	✓
RMH15000HM-PUB	130-1300	490	550	1300	15000	Hydraulic	✓	✓
RMH15000HM-PUB	150-1600	490	550	1300	15000	Hydraulic	✓	✓
RMH20000HM-PUB	150-1600	490	550	1300	20000	Hydraulic	✓	✓
RMH25000HM-PUB	150-1600	490	550	1300	25000	Hydraulic	✓	✓