

DAMS Long Conveyor Packaging Machine with Feeding / DUKB-50



TECHNIKAL FEATURES	
MAKS. POWER	3 Kw
VOLTAGE	380 V
MAX.CURRENT	25 A
KONTROL	PLC-Touch Screen
Compressor Air Requirement	5-6 Bar

MACHINE FEATURES	
CAPACITY MAX.	180 pcs/mn
MACHINE WIDTH	1920 mm
MACHINE LENGTH	4150 mm
MACHİNE HEIGHT	1690 mm
MACHINE WEIGHT	950 Kg
PACKAGE WIDTH	20 - 140 mm
PACKAGE LENGHT	100- 250 mm
PACKAGE HEIGHT	20 - 60 mm
CAPACITY MAX.	180 pcs/mn
MAX. BOBBİN WIDTH	500 mm
CELLOPHANE BOBBİN DIAMETER MAX.	350 mm
BOBBİN INTERNAL DIAMETER	3 "

O DAMS



GENERAL SPESIFICATIONS

- Roll, Sandwich Hamburger and similar sized products and Francala Bread are individually wrapped.
- Our machine has a servo motor system.
- Thanks to the touch screen and PLC on the machine, product package length, photocell adjustment and machine speed can be adjusted as desired.
- There is a sensor control system that prevents jamming of the product. If the product location is not correct, it stops the machine.
- All surfaces and covers that are in contact with the product in the machine are made of 304 quality chrome-nickel metal.
- Rotating jaw system.
- It packs 115 products per minute (roll, sandwich hamburger and similar products), and 83 products per minute in Francala Bread.
- It easy to use.
- Optionally, it is produced so that a coding device can be mounted on the machine.
- Cellophane bobbin is easy to disassemble and install, the place where it is mounted is an air system and PLC controlled shaft.
- Since the bottom sealing system of the packaging is pneumatic and PLC controlled, the settings of the packaging material are made without wasting time.

Best Regards,

DAMS® MACHINE

DAMS
Offers only perfection
All around the world













