

DAMS Mobile Jaw Packaging Machine with Slicer and Feeder / DGYR - 50



TECHNICIAL SPECIFICATIONS		
MAX. POWER	8 Kw	
VOLTAGE	380 V	
MAX. CURRENT	21 A	
CONTROL	PLC-Touch Screen	
Compressor Air Requirement	5-6 Bar	

MACHINE FEATURES	
CAPACITY MAX.	40 adet/dk.
MACHINE WIDTH	5250 mm
MACHINE LENGTH	6440 mm
MACHINE HEIGHT	1670 mm
MACHINE WEIGHT	2100 Kg
PACKAGE WIDTH	60 - 250 mm
PACKAGE LENGTH	200- 600 mm
PACKAGE HEIGHT	20-130 mm
MAX. BOBBIN WIDTH	700 mm
MAX. Cellophane COIL DIAMETER	350 mm
INTERNAL DAMETER OF THE BOBİNE	3 "



GENERAL CHARACTERISTICS AND INFORMATION FOR USE

Sandwich and hamburgers coming from the cooling tower or in bulk are placed manually between the product sorting slides with the help of two personnel.

When the products are divided into groups, the numbers are checked with the sensors, and if there are missing rows, they wait until the order is completed.

The queues are divided into groups by the help of two flaps, and the number of packages depends on desired grouping (sandwich 4, 5, 6, Hamburger 4, 6, 8).

Here, the products are placed between the product pushers of the packaging machine with the help of a push rod.

Product pushers take products to the enveloping unit and allow them to be packaged. Our packaging machine is servo controlled.

Our machine has PLC controlled panel display. All settings, product tracking, failures and warnings can be monitored from this screen..

The glue discs are opened and closed from the screen. Automatically close even when it is switched on.

It has an empty package control system. If you do not disable this system, absolutely empty packaging will not come out of the machine.

The machine is photocell and thus does not allow the packaging waste.

Quick blot control, packaging waste is reduced to almost nothing compared to their counterparts in the first adjustment.

With mobile jaw system.

Food suitable belts and 304 Cr-Ni material was used on the product contact surfaces.

When the machine is turned off, the disc with the heater automatically opens and does not damage the package, it does not dissolve and the packaging loss is close to zero.

The packaging capacity is between 10 and 35 pcs/min. This may vary depending on the product. Our machine; is suitable for the operation of the printing device such as production date serial number-expiration date on package. This device is optional.

Note: Our machine can pack products such as pita, bagel, khaleb - shawarma bread etc.

Best Regards,



DAMS

All around the world

Offers only perfection











