



FAS

Astar Silindir Makinesi

176 cm

136 cm

KG

FAS 100X125 : 735 KG
 FAS 150X125 : 780 KG
 FAS 100X150 : 990 KG
 FAS 150X150 : 1020 KG

FAS 100X125 : 100 cm
 FAS 150X125 : 106 cm
 FAS 100X150 : 100 cm
 FAS 150X150 : 106 cm

TEKNİK / TECHNICAL		FAS 100X125	FAS 150X125	FAS 100X150	FAS 150X150
MİRDANE ROLL	AYAK PEDALI / FOOT PEDAL	YOK / NO	YOK / NO	YOK / NO	YOK / NO
	ÇAP / DIAMETER	125 mm	125 mm	150 mm	150 mm
	GENİŞLİK / WIDTH	100 mm	150 mm	100 mm	150 mm
	AÇIKLIK / OPENING DISTANCE	20 mm	20 mm	25 mm	25 mm
	DEVİR / RPM	13,5 d/dk	13,5 d/dk	11 d/dk	11 d/dk
SARMA MAKARASI / WINDING REEL	VAR / YES	VAR / YES	VAR / YES	VAR / YES	
SOĞUTMA SİSTEMİ / COOLING SYSTEM	VAR / YES	VAR / YES	VAR / YES	VAR / YES	
OTOMATİK YAĞLAMA / AUTOMATIC LUBRICATION	VAR / YES	VAR / YES	VAR / YES	VAR / YES	

ELEKTRİK / ELECTRICITY		FAS 100X125	FAS 150X125	FAS 100X150	FAS 150X150
ANA MOTOR MAIN ENGINE	GÜÇ / POWER	5,5 KW	5,5 KW	5,5 KW	5,5 KW
	FAZ / PHASE	380V TRI	380V TRI	380V TRI	380V TRI
	YÖN / DIRECTION	ÇİFT/DOUBLE	ÇİFT/DOUBLE	ÇİFT/DOUBLE	ÇİFT/DOUBLE
	DEVİR / RPM	1400 d/dk	1400 d/dk	1400 d/dk	1400 d/dk
EK MOTOR 1 EXTRA ENGINE 1	GÜÇ / POWER	0,37 KW	0,37 KW	0,37 KW	0,37 KW
	FAZ / PHASE	380V TRI	380V TRI	380V TRI	380V TRI
	YÖN / DIRECTION	ÇİFT/DOUBLE	ÇİFT/DOUBLE	ÇİFT/DOUBLE	ÇİFT/DOUBLE
	DEVİR / RPM	1400 d/dk	1400 d/dk	1400 d/dk	1400 d/dk
EK MOTOR 2 EXTRA ENGINE 2	GÜÇ / POWER	0,37 KW	0,37 KW	0,37 KW	0,37 KW
	FAZ / PHASE	380V TRI	380V TRI	380V TRI	380V TRI
	YÖN / DIRECTION	ÇİFT/DOUBLE	ÇİFT/DOUBLE	ÇİFT/DOUBLE	ÇİFT/DOUBLE
	DEVİR / RPM	1400 d/dk	1400 d/dk	1400 d/dk	1400 d/dk
İNVERTÖR / INVERTER	OPSİYON	OPSİYON	OPSİYON	OPSİYON	
PLC	YOK / NO	YOK / NO	YOK / NO	YOK / NO	