



Electric exhaust duct cleaning equipment

It performs the cleaning of the grease accumulated in exhaust ducts. It sprays active foam and brushes the duct. After a few minutes you can rinse for a perfect finish.

- It incorporates the **Proaxis system**, which minimizes shaft breakage during cleaning.
- **Connected to the ifoam range of equipment**, it allows you to inject the active foam which adheres to the entire surface of the duct.
- The **remote control** allows the equipment to be used by a single operator.

HMI screen

Control the equipment from the touch screen.

Connection for ifoam



ELECTRIC

For ducts up to

600 mm

Hose length

15 m

Brushes

With different materials and sizes to adapt to any duct. Also double row brushes for effective cleaning in **square ducts**.



INCLUDED ACCESORIES



**FLEXIBLE ROTARY SHAFT
+ LIQUID INJECTION.**
Ø 12 mm and length 15 m


COD. AC3101212



**WRIST REMOTE
CONTROL**

COD. AC3303605

CONSUMABLES



PACK x5 SQUARE DUCTS

For square ducts
Measurements:
Ø250, 300, 350, 400 & 500 mm.

COD. CP 2300511

PACK x5 PBT

Grease grade 2 (medium soiling).
Measurements:
Ø200, 300, 400, 500 & 600 mm.

COD. CP1203030

**PACK x5 MIXED: STEEL
+ NYLON.** Grease grade 3
(High soiling).
Ø200, 300, 400, 500 y 600 mm

COD. CP1302828



COMEGRAS

Ultraconcentrated
degreaser.
10 kg | 22 lb Jerrycan

COD. PQ8100122

OPTIONAL ACCESORIES



CENTERING DEVICE

Recomended to clean ducts
from 400 to 600 mm

COD. AC3101500

FEATURES

eon

Power supply	220 V - 50 Hz 110 V - 60 Hz
Engine power	370 W máxima
Engine rotation speed	0 - 3000 r.p.m.
Engine operating speed	0 - 500 r.p.m.
Noise level	Less than 70 dB
Direction of rotation	Right / Left
Control system	Electric
Control panel	HMI screen
Structural material	Stainless steel and HDPE
Dimensions (H x W x D)	962 x 365,5 x 992 mm 38 x 14,39 x 39 inches
Weight	60 kg 132 lb
Hose length:	15 m // 49 ft