

Catalogue
FOOD SERVICE
Chapter
DISHWASHING

Specific model
CCO-160 PACK L CW 400V 3N 50Hz

19068305 14/06/2022

DENOMINATION:

Compact rack conveyor 160 racks/hour with entrance from the feft for cold water with antisplash and drying tunnel

DESCRIPTION :

"- All the main parts are manufactured in AISI-304 anti-corrosion stainless steel: tanks, washing and rinsing arms, rinsing jets, doors, basket conveyance system, boiler and metal tubes.
- Upwards-opening double panel door.
- Tank tray filters made of AISI-304 stainless steel, easy to access and remove for cleaning and access to the tank.
- Safety filter for pump suction.
- Rinsing boiler with heat insulation.
- Easy access for installation. Electrovalve located on one side (no need to remove panels to connect the machine).
- Electrical panel designed for easy connection of dosers for liquid and solid detergents, rinse aid, limit switches, supplementary emergency stop button.
- Washing arms easily removable as a set, for cleaning, with a plug on each branch providing access for cleaning inside.
- Rinse jets easily dismountable and removable.
- System of electronic regulation of speeds by means of frequency shifter.
- Configurable electronic temperature control:
- Wash (50 - 65 °C)
- Rinse (70 - 85 °C)
- Guarantor of rinse at 85 °C.
- Pressure regulator for flow control.
- Emergency stop button incorporated.
- Extra anti-entrapment protection system at the entrance, mounted on the AS-260 splash guard supplement (optional).
- Open door blocking system.
- IPX4 protection system.
- System for detection of blockage of conveyor carriage and automatic reverse function.
- Energy-saving system: reduces consumption by halting operation of the pumps, and by passing the heating of the rinse to stand-by mode (70 °C).
- Auto-timer which deactivates the conveyor motor after a pre-set period of inactivity (10 minutes)."
"´- High-power washing system with 4 upper and 4 lower washing branches.
- Double effect rinse."
Entry through the left part of the machine.
CW: Model prepared for connection with cold water from the network (input temperature <(><<)>50 ºC.).
IMPORTANT:
- Anti-splash (AS-260) and drying tunnel (CDT-600) are included.


STANDARD OPTIONS :

- Drying tunnel
- Anti-splash guard supplement (enter)

POSSIBLE ACCESSORIES :

- BASKETS
- MODULAR ELEMENTS

DIMENSIONS



X Width	2040	mm	X Gross width	2160	mm
Y Depth	790	mm	Y Gross depth	955	mm
Z Height	1930	mm	Z Gross height	2200	mm
Net Weight	296,0	kg	Gross Weight	427,0	kg
Net volume	2,225	m3	Gross volume	4,538	m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Engine power	1,95 kW
Electric power	41,150 kW
Amperage (A)	65,8
Heating power	39,00 kW
Voltage	400V - 3N
Electric frequency	50Hz

WATER TECHNICAL SPECIFICATIONS

Pressure	H2O: 200-400kPa(2-4bar)
Water max consumption	240,00 L/h

CONNECTIONS TECHNICAL SPECIFICATIONS

Three-phase +N 400V wiring	4X25+T - 100 A
Drain 1 diameter	38

OTHERS

Noise level	72,00 dB



Catalogue
FOOD SERVICE
Chapter
DISHWASHING

Specific model
CCO-160 PACK L CW 400V 3N 50Hz

19068305 14/06/2022

- ENTRY-EXIT TABLES
- BASKETS FOR DISHWASHERS
- BASKETS FOR GLASSES

SUPPLIED ACCESSORIES:

- 19000484 Standard basket 2
- 19000487 Basket for 16/18 dishes 2
- 19000488 Baskets for 16 glasses and cups with 110 mm diameter and 105 mm height 1
- 19036306 Standard basket with dense base 1