HIGH POWERFLAME TEMPERATURE & SURFACE AREA



GET TO WORK

- o Single-click hose connection, thanks to the fast connector.
- o Readily available flame thanks to synchronised piezo ignition, with a single press on the trigger.
- o Interchangeable burners, with no tools needed.
- o Easy self-maintenance: changing the trigger / piezo-ignition also requires no tools.

POWER

Offering a high level of performance with its large flame, the WIZZ gun has a range of burners from 50 to 150 kW (171 000 to 511 500 BTU/h).

USER COMFORT

- o Very lightweight (about 650 g), to reduce the risk of musculoskeletal disorders (MSDs).
- Ready-to-use gun, operational in less than a minute, comes in a carrying case.
- Spare trigger / piezo-ignition included in the pack.

- o Control power through the level of pressure exerted on the trigger.

ENVIRONMENTAL APPROACH

The safety-handle that equips the WIZZ gun contributes to a significant reduction in gas consumption and therefore:

- o reduces CO2 emissions.
- o avoids the risk of causing accidental fires on worksites and related harm to people and property.



• Response in less than 24 hours.

SAFETY

- O Safe ignition with low gas flow.
- o Three-position marking: changing burner, storage, ignition.
- o Safety handle (the gun switches off when the operator releases the handle).
- o Professional quality rubber hose to ISO 3821 standard.
- o Gun specially designed to provide optimum heat resistance.














| 6 BURNERS Cat. No. | 150WL400 | 150WL200 | 100WL600 | 100WL400 | 100WL200 | 50W L200 |
|--|----------------|----------------|----------------|----------------|----------------|---------------|
| Ø BURNER (mm) | 70 | 70 | 60 | 60 | 60 | 50 |
| (in) | 2.75 | 2.75 | 2.36 | 2.36 | 2.36 | 1.97 |
| WEIGHT (g) | 310 | 225 | 325 | 300 | 220 | 205 |
| CONS. (g/h) | 10860 | 10860 | 7390 | 7390 | 7390 | 3910 |
| (lb/h) | 23.95 | 23.95 | 16.30 | 16.30 | 16.30 | 8.60 |
| POWER (kW /4 bar) (BTU/h - 58 psi) | 150 511 500 | 150 511 500 | 100 341 000 | 100 341 000 | 100 341 000 | 50 171 000 |
| L FLAME (mm) | 1000 | 1000 | 800 | 800 | 800 | 650 |
| (in) | 39.37 | 39.37 | 31.50 | 31.50 | 31.50 | 25.59 |
| Ø FLAME (mm) | 130 | 130 | 120 | 120 | 120 | 110 |
| (in) | 5.12 | 5.12 | 4.72 | 4.72 | 4.72 | 4.33 |











Distributor stamp