

# Elle Kumandalı VİBRASYONLU SİLİNDİRLER

*Walk Behind Vibrating Tandem Rollers*



<b>Teknik Özellikler / Technical Specifications</b>	<b>PDR600</b>	<b>PDR600S</b>	<b>Birim / Unit</b>
Nakliye Ebatları (ExBxY) / Transportation Dimensions (WxLxH)	830X1220X1870	830X1220X1870	mm
Nakliye Ağırlığı / Transportation Weight	583	617	kg
Tambur Geniřlięi / Drum Width	600	600	mm
Su Deposu / Water Tank	32	32	lt
Yaę Deposu / Oil Tank	32	32	lt
Santrifüj Kuvveti / Centrifugal Force	20	20	kN
Yürüme Hızı (İleri - Geri) / Speed (Forward- Back)	2,6	2,6	km/saat / km/h
Tırmanma Eğimi / Gradeability	40	40	%
Motor (DIN ISO 1585) / Engine	Dizel / Diesel, 7,5 HP *	Dizel / Diesel, 7,5 HP, Marşlı* / Electric Starter*	-
Yakıt Deposu / Fuel Tank	4,3	4,3	lt
Yakıt Sarfiyatı / Fuel Consumption	1,7	1,7	lt/saat / lt/h

\*Alternatif Motor seçenekleri için lütfen bilgi alınız. / Please ask for the alternative engine options

