







Offers High Quality Range of Pneumatically Driven Airless Spray Painting Machines for professional painting applications, industries and painting contractors.



SURFACE COATING EQUIPMENTS
AN ISO 9001:2018 CERTIFIED COMPANY

PNEUMATICALLY
DRIVEN
MEDIUM DUTY
AIRLESS PAINT
SPRAY MACHINE



+91-9423506457/9422082377/020-66306016

Sales@jaguarequipments.com

(#) www.jaguarequipments.com

C301

TECHNICAL SPECIFICATION

➤ MODEL: C-301
➤ RATIO: 30:1

➤ OUTPUT PER MINUTES (LTRS) FREE FLOW: 5.5

➤ AIR INLET PRESSURE MAX. (KG/CM2): 7 / 101.5 PSI

➤ OUTPUT FLUID PRESSURE MAX. (KG/CM2): 210 / 3045 PSI

➤ FLUID INLET SIZE: 1/2" BSP
➤ FLUID OUTLET SIZE: 1/4" BSP

➤ AIR INLET: 1/2" BSP
➤ WEIGHT: ~50 KG

TYPICAL FLUID HANDLED

- ➤ MEDIUM VOLUME SOLID PAINTS
- ➤ MEDIUM VISCOSITY COATINGS
- ➤ LOW SOLVENT COATINGS
- ➤ EPOXY PAINTS
- ➤ ENAMEL / HR PAINT
- ➤ POLYURETHANE COATINGS
- ➤ ZINC BASE COATINGS

APPLICATIONS

- > PRE ENGINEERING BUILDING STRUCTURAL COATING
- > BRIDGES AND ROOF COATING
- > RAIL CAR AND TRANSPORT VEHICLES
- ➤ CORROSION PREVENTIVE COATING
- ➤ POWER PLANTS & HEAVY FABRICATION
- > FOUNDRIES
- > INJECTION GROUTING



RUST PROOF STAINLESS STEEL HYDRAULIC CIRCUIT WITH HIGH FLOW RATE DETACHABLE SUCTION PORT FOR EASY SERVICE WITHOUT SPECIAL TOOLS



COMPACT & LIGHT WEIGHT SPRAY GUN SAFETY TRIGGER LOCK TWO FINGER TRIGGER 360° SWIVEL





CARTRIDGE TYPE THROAT SEAL HOUSING FOR QUICK AND EASY REPLACEMENT OF SEALS



AIR FILTER REGULATOR WITH SAFETY VALVE TO PREVENT MOTOR FROM RECEIVING EXCESS PRESSURE



PLOT NO 127, SECTOR NO.10 PCNTDA, MIDC BHOSARI, PUNE, MAHARASHTRA, INDIA-411026