ÇM 004

PASLANMAZ ÇELİK ZEYTİN ELEME MAKİNASI

STAINLESS STEEL OLIVE SIEVING MACHINE



Makina farklı ebatlardaki zeytinin sınıflandırılması işleminde kullanılır. Zeytin makineye bir yükleme elevatörü sayesinde iletilir. Makina üzerinde zeytinleri kayışlar üzerinde homojen olarak dağıtmak ve yaprak vb. yabancı maddeleri ayırmak için fanlı dağıtıcı bant sistemi bulunmaktadır. Zeytinlerin makina üzerinde boylarına göre sınıflandırıldığı bölmeler arası mesafeler kademesiz olarak ayarlanabildiği için, istenilen bölgeden istenilen kalibrede ürünü alabilmek mümkündür. Makinada kullanılan pano ve buatlar IP 65 sınıfı olup su geçirmez malzemeden imal edilmiştir. Makina tamamen paslanmaz çelik olarak imal edilmiştir.

The machine is used in classification of products in different sizes. Product is transmitted to the machine by a loading elevator. There is a fan- distributor band system to separate leaves etc., foreign materials and distribute products homogenously on the band. As the clearance between the sections where products are classified according to their sizes can be adjusted ungradually on the machine, it is possible to receive the desired product caliber in the desired section. Panels and junction boxes used on the machine are class IP 65 and made of water proof material. The machine is completely made of stainless steel.

TEKNİK VERİLER / TECHNICAL INFORMATION

	ÇM004-4M	ÇM004-6M	ÇM004-8M	ÇM004-10M	ÇM004-12M
Uzunluk (Makine + Elevatör) Lenght (Machine + Elevator)	4406 mm / 5800 mm	6297 mm / 7690 mm	8200 mm / 9593 mm	10200 mm / 12052 mm	12200 mm / 14052 mm
Uzunluk (Eleme Boyu) Lenght (Sieving Lenght)	3595 mm	5420 mm	7425 mm	9430 mm	11450 mm
Genişlik Width	1152 mm	1150 mm	1245 mm		
Yükseklik (Kasa platformlu model yüksekliği) Height (Height of crate platform model)	1346 mm / 2010 mm	1435 mm / 2075 mm	1400 mm / 2075 mm	1420 mm / 2075 mm	1450 mm / 2075 mm
Motor Gücü (Makine + Elevatör + Fan gücü) Engine Power (Machine + Elevator + Fan)	0,75 kw + 0,37 kw + 0,14 kw				
Su Tüketimi Water Consumption	-				
Kapasite Capacity **(Min/Max)**	2500 kg / s(h)	3500 kg / s(h)		4500 kg / s(h)	
PU Kayış Adedi Quantity of PU Belt	18 adet / units	20 adet / units		24 adet / units	
Opsiyonel Özellik Optionals	**İlave ayırma gözü - Yükleme elevatörü - * Kasa platformlu model** / Additional sieving section - Loading elevator - * Crate platform model				

* Kasa Platformlu Model özel olarak imal edilmektedir / Crate Platform Model manufactured upon special request

ÇM 004

PASLANMAZ ÇELİK ZEYTİN ELEME MAKİNASI
STAINLESS STEEL OLIVE SIEVING MACHINE

cinarlimakina.com



ÖZELLİKLER / FEATURES

- IP 65 plastik kumanda panosu (Hensel)
- 220 V / 50 HZ
- Elevatör ve zeytin eleme makinasında birbirinden bağımsız elektronik hız kontrol sistemi
- AISI 304L paslanmaz çelik gövde
- Plastik gövdeli paslanmaz çelik yataklı rulmanlar
- Termik röleli koruma
- Elektronik hız kontrol sistemi (Schneider)
- Tüm bantlar FDA'ya uygun PVC
- FDA'ya uygun 10mm PU yuvarlak kayış
- Yükleme elevatörü
- AISI 304 paslanmaz çelik tekerlek
- Göz mesafesi ayarlayabilme imkanı
- Göz sayısını değiştirebilme imkanı
- Yaprak vb. yabancı madde temizleme fanı
- PU kayış ömrünü uzatan 400mm çapında plastik merdaneler
- Kayış gergi mekanizması
- Sonsuz dişli redüktör

- *Ip 65 plastic control panel (Hensel)*
- *220 V / 50 HZ*
- *Independent electronic speed control system on elevator and grading machine*
- *AISI 304L stainless steel body*
- *Bearings with plastic body and stainless steel housing*
- *Protection with thermic relay*
- *Electronic speed control system (Schneider)*
- *All the bands are made of PVC conforming to FDA*
- *10mm round belt conforming to FDA*
- *Loading elevator*
- *AISI 304 stainless steel caster*
- *Adjustable section distance*
- *Section number may be changed*
- *Leaf, etc. foreign material cleaning fan*
- *400 mm diameter of plastic rollers that extends life of PU belt*
- *Belt tensioning mechanism*
- *Worm gear reducer*

